



MVG (快速接头)



MVG (螺纹转换接头)




ARF 3P *




ARF



AR1 / AR2



AR1 / AR2



AR3

接头											
型号	编号	流量		最大压力		额定温度	进水口	接头	型号/ 插头	重量 g	件/箱
		l/min	gpm	bar	psi						
MVG (快速接头)	021200000	40	10,6	280	4060	150°C	1/2" GF	1/2" GF	MVG 4	119	20
	021200010	40	10,6	280	4060	150°C	1/2" GM	1/2" GF	MVG 5	112	20
	021200020	40	10,6	280	4060	150°C	3/8" GF	1/2" GF	MVG 6	104	20
	021200030	40	10,6	280	4060	150°C	1/4" GF	1/2" GF	MVG 7	113	20
	021200040	40	10,6	280	4060	150°C	3/8" GM	1/2" GF	MVG 8	112	20
	021200050	40	10,6	280	4060	150°C	1/4" GM	1/2" GF	MVG 9	103	20
MVG (螺纹转换接头)	0212000100	40	10,6	280	4060	150°C	1/2" GF	1/2" GM	MVG 04	63	20
	0212000110	40	10,6	280	4060	150°C	1/2" GM	1/2" GM	MVG 05	71	20
	0212000120	40	10,6	280	4060	150°C	3/8" GF	1/2" GM	MVG 06	57	20
	0212000130	40	10,6	280	4060	150°C	1/4" GF	1/2" GM	MVG 07	65	20
	0212000140	40	10,6	280	4060	150°C	3/8" GM	1/2" GM	MVG 08	58	20
	0212000150	40	10,6	280	4060	150°C	1/4" GM	1/2" GM	MVG 09	57	20
ARF 3P *	4100400001	40	10,6	280	4060	150°C	1/2" GF	M22 x 1,5 F	短	127	20
	4100400000	40	10,6	280	4060	150°C	1/2" GM	M22 x 1,5 F	短	127	20
	300305	40	10,6	280	4060	150°C	3/8" GF	M22 x 1,5 F	短	107	20
	300303	40	10,6	280	4060	150°C	1/4" GF	M22 x 1,5 F	短	117	20
	300304	40	10,6	280	4060	150°C	3/8" GM	M22 x 1,5 F	短	116	20
	300302	40	10,6	280	4060	150°C	1/4" GM	M22 x 1,5 F	短	105	20
ARF	0115711020	40	10,6	280	4060	150°C	1/4" GM	M22 x 1,5 M	长	52	20
	150024	40	10,6	280	4060	150°C	3/8" GM	M22 x 1,5 M	长	60	20
	150050	40	10,6	280	4060	150°C	1/2" GM	M22 x 1,5 M	长	58	20
	150005	40	10,6	280	4060	150°C	1/4" GF	M22 x 1,5 M	长	65	20
	1500180	40	10,6	280	4060	150°C	3/8" GF	M22 x 1,5 M	长	55	20
	150049	40	10,6	280	4060	150°C	1/2" GF	M22 x 1,5 M	长	80	20
	0212003660	40	10,6	280	4060	150°C	M22 x 1,5 M	M22 x 1,5 M	长	52	20
	0212003600	40	10,6	280	4060	150°C	1/2" GF	M22 x 1,5 M	短	47	20
	0212003610	40	10,6	280	4060	150°C	1/2" GM	M22 x 1,5 M	短	57	20
	0212003620	40	10,6	280	4060	150°C	3/8" GF	M22 x 1,5 M	短	43	20
	0212003630	40	10,6	280	4060	150°C	1/4" GF	M22 x 1,5 M	短	50	20
	0212003640	40	10,6	280	4060	150°C	3/8" GM	M22 x 1,5 M	短	50	20
	0212003650	40	10,6	280	4060	150°C	1/4" GM	M22 x 1,5 M	短	45	20
0115712020	40	10,6	280	4060	150°C	M22 x 1,5 F	M22 x 1,5 M	短	82	20	
AR1(A)	0212002220 (A)	40	10,6	280	4060	150°C	1/4" GF	QC - F	-	65	20
AR1(B)	380603 (B)	40	10,6	280	4060	150°C	1/4" NPT M	QC - M	-	31	20
	380602 (B)	40	10,6	280	4060	150°C	1/4" NPT F	QC - M	-	32	20
AR2(A)	0212002300 (A)	40	10,6	280	4060	90°C	3/8" GF	QC - F	-	120	20
	0204002310 (A)	40	10,6	280	4060	90°C	3/8" NPT F	QC - F	-	120	20
	0204002320 (A)	40	10,6	280	4060	90°C	3/8" GM	QC - F	-	110	20
	0204002320 (A)	40	10,6	280	4060	90°C	3/8" NPT M	QC - F	-	110	20
	0204002320 (A)	40	10,6	280	4060	90°C	M22 x 1,5 M	QC - F	-	110	20
AR2(B)	0121730040 (B)	40	10,6	280	4060	90°C	3/8" NPT M	QC - M	-	40	20
	0121730050 (B)	40	10,6	280	4060	90°C	3/8" NPT F	QC - M	-	47	20
	0121730090 (B)	40	10,6	280	4060	90°C	3/8" GF	QC - M	-	47	20
	0121730060 (B)	40	10,6	280	4060	90°C	3/8" GM	QC - M	-	40	20
	0121730200 (B)	40	10,6	280	4060	90°C	1/4" GF	QC - M	-	35	20
AR3	0212006150(1)	45	12,0	250	3600	150°C	1/4" GM	QC - F	-	31	5
	02121720120(2)	45	12,0	250	3600	150°C	1/4" GF	QC - M	-	32	5

* 直径14mm短接头